



DEPARTMENT OF COMMERCE

International Trade Administration

[A-122-869]

Tin Mill Products from Canada: Final Affirmative Determination of Sales at Less Than Fair Value and Final Negative Determination of Critical Circumstances

AGENCY: Enforcement and Compliance, International Trade Administration, Department of Commerce.

SUMMARY: The U.S. Department of Commerce (Commerce) determines that imports of tin mill products from Canada are being, or are likely to be, sold in the United States at less than fair value (LTFV). The period of investigation January 1, 2022, through December 31, 2022.

DATES: Applicable [INSERT DATE OF PUBLICATION IN THE *FEDERAL REGISTER*].

FOR FURTHER INFORMATION CONTACT: Yang Jin Chun, AD/CVD Operations, Office VI, Enforcement and Compliance, International Trade Administration, U.S. Department of Commerce, 1401 Constitution Avenue, NW, Washington, DC 20230; telephone: (202) 482-5760.

SUPPLEMENTARY INFORMATION:

Background

On August 22, 2023, Commerce published in the *Federal Register* its preliminary affirmative determination in the LTFV investigation of tin mill products from Canada, in which it also postponed the final determination until January 4, 2024.¹ We invited interested parties to comment on the *Preliminary Determination*.

A summary of the events that occurred since Commerce published the *Preliminary*

¹ See *Tin Mill Products from Canada: Preliminary Affirmative Determination of Sales at Less Than Fair Value, Preliminary Negative Determination of Critical Circumstances, Postponement of Final Determination, and Extension of Provisional Measures*, 88 FR 57081 (August 22, 2023) (*Preliminary Determination*), and accompanying Preliminary Decision Memorandum.

Determination, as well as a full discussion of the issues raised by parties for this final determination, may be found in the Issues and Decision Memorandum.² The Issues and Decision Memorandum is a public document and is on file electronically via Enforcement and Compliance's Antidumping and Countervailing Duty Centralized Electronic Service System (ACCESS). ACCESS is available to registered users at <https://access.trade.gov>. In addition, a complete version of the Issues and Decision Memorandum can be accessed directly at <https://access.trade.gov/public/FRNoticesListLayout.aspx>.

Scope of the Investigation

The products covered by this investigation are tin mill products from Canada. For a complete description of the scope of this investigation, *see* Appendix I.

Scope Comments

During the course of this investigation, Commerce received scope comments from parties. Commerce issued a Preliminary Scope Decision Memorandum to address these comments and set aside a period of time for parties to address scope issues in scope-specific case and rebuttal briefs.³ We received comments from parties on the Preliminary Scope Decision Memorandum, which we address in the Final Scope Decision Memorandum.⁴ We did not make any changes to the scope of the investigation from the scope published in the *Preliminary Determination*, as noted in Appendix I.

Verification

Commerce verified the information relied upon in making its final determination in this investigation, consistent with section 782(i) of the Tariff Act of 1930, as amended (the Act). Specifically, Commerce conducted on-site verifications of the information and data on home

² See Memorandum, "Issues and Decision Memorandum for the Final Affirmative Determination of Sales at Less Than Fair Value and Final Negative Determination of Critical Circumstances in the Investigation of Tin Mill Products from Canada," dated concurrently with, and hereby adopted by, this notice (Issues and Decision Memorandum).

³ See Memorandum, "Preliminary Scope Decision Memorandum," dated August 16, 2023 (Preliminary Scope Decision Memorandum).

⁴ See Memorandum, "Final Scope Decision Memorandum," dated concurrently with this memorandum (Final Scope Decision Memorandum).

market sales, U.S. sales, and cost of production submitted by ArcelorMittal Dofasco G.P.

(Dofasco).⁵

Analysis of Comments Received

All issues raised in the case and rebuttal briefs submitted by interested parties in this investigation are addressed in the Issues and Decision Memorandum. A list of the issues addressed in the Issues and Decision Memorandum is attached to this notice as Appendix II.

Changes Since the *Preliminary Determination*

We made certain changes to the margin calculation for Dofasco since the *Preliminary Determination*. For a discussion of these changes, *see* the Issues and Decision Memorandum.

All-Others Rate

Section 735(c)(5)(A) of the Act provides that the estimated weighted-average dumping margin for all other producers and exporters not individually investigated shall be equal to the weighted average of the estimated weighted-average dumping margins established for individually investigated exporters and producers, excluding rates that are zero, *de minimis*, or determined entirely under section 776 of the Act, *i.e.*, facts otherwise available.

In this investigation, Commerce calculated an individual estimated weighted-average dumping margin for the sole mandatory respondent, Dofasco, that is not zero, *de minimis*, or based entirely on facts otherwise available. Consequently, Commerce assigned the estimated weighted-average dumping margin calculated for Dofasco to all other producers and exporters of the merchandise under consideration, pursuant to section 735(c)(5)(A) of the Act.

Final Negative Determination of Critical Circumstances

In accordance with section 735(a)(3) of the Act and 19 CFR 351.206, Commerce continues to find that critical circumstances do not exist for all companies in Canada. For a full description of the methodology and results of Commerce's critical circumstances analysis, *see*

⁵ *See* Memoranda, "Sales Verification Report," dated November 1, 2023; and "Verification of the Cost Response of ArcelorMittal Dofasco G.P.," dated November 2, 2023.

the Issues and Decision Memorandum.⁶

Final Determination

Commerce determines that the following estimated weighted-average dumping margins exist:

Exporter/Producer	Estimated Weighted-Average Dumping Margin (percent)
ArcelorMittal Dofasco G.P.	5.27
All Others	5.27

Disclosure

Commerce intends to disclose the calculations performed in connection with this final determination to interested parties within five days of any public announcement or, if there is no public announcement, within five days of the date of publication of this notice, in accordance with 19 CFR 351.224(b).

Continuation of Suspension of Liquidation

In accordance with section 735(c)(1)(B) of the Act, Commerce will instruct U.S. Customs and Border Protection (CBP) to continue to suspend liquidation of all entries of subject merchandise, as described in Appendix I of this notice, which were entered, or withdrawn from warehouse, for consumption on or after August 22, 2023, the date of publication of the *Preliminary Determination* in the *Federal Register*. These suspension of liquidation instructions will remain in effect until further notice.

Pursuant to section 735(c)(1)(B)(ii) of the Act and 19 CFR 351.210(d), upon the publication of this notice, we will instruct CBP to require a cash deposit for estimated antidumping duties for such entries as follows: (1) the cash deposit rate for the respondent listed in the table above is the company-specific estimated weighted-average dumping margin listed for

⁶ See Issues and Decision Memorandum at 3.

the respondent in the table; (2) if the exporter is not the respondent listed in the table above, but the producer is, then the cash deposit rate is the company-specific estimated weighted-average dumping margin listed for the producer of the subject merchandise in the table above; and (3) the cash deposit rate for all other producers and exporters is the all-others estimated weighted-average dumping margin listed in the table above.

U.S. International Trade Commission Notification

In accordance with section 735(d) of the Act, Commerce will notify the U.S. International Trade Commission (ITC) of its final affirmative determination of sales at LTFV. Because Commerce's final determination is affirmative, in accordance with section 735(b)(2) of the Act, the ITC will make its final determination as to whether the domestic industry in the United States is materially injured, or threatened with material injury, by reason of imports or sales (or the likelihood of sales) for importation of tin mill products no later than 45 days after this final determination. If the ITC determines that such injury does not exist, this proceeding will be terminated, all cash deposits posted will be refunded, and suspension of liquidation will be lifted. If the ITC determines that such injury does exist, Commerce will issue an antidumping duty order directing CBP to assess, upon further instruction by Commerce, antidumping duties on all imports of the subject merchandise entered, or withdrawn from warehouse, for consumption on or after the effective date of the suspension of liquidation, as discussed in the "Continuation of Suspension of Liquidation" section above.

Administrative Protective Order

This notice serves as the only reminder to parties subject to an administrative protective order (APO) of their responsibility concerning the disposition of proprietary information disclosed under APO in accordance with 19 CFR 351.305(a)(3). Timely written notification of the return or destruction of APO materials or conversion to judicial protective order is hereby requested. Failure to comply with the regulations and terms of an APO is a sanctionable violation.

Notification to Interested Parties

This final determination and notice are issued and published in accordance with sections 735(d) and 777(i) of the Act and 19 CFR 351.210(c).

Dated: January 4, 2024.

Abdelali Elouaradia,
Deputy Assistant Secretary for Enforcement and Compliance.

Appendix I

Scope of the Investigation

The products within the scope of this investigation are tin mill flat-rolled products that are coated or plated with tin, chromium, or chromium oxides. Flat-rolled steel products coated with tin are known as tinplate. Flat-rolled steel products coated with chromium or chromium oxides are known as tin-free steel or electrolytic chromium-coated steel. The scope includes all the noted tin mill products regardless of thickness, width, form (in coils or cut sheets), coating type (electrolytic or otherwise), edge (trimmed, untrimmed or further processed, such as scroll cut), coating thickness, surface finish, temper, coating metal (tin, chromium, chromium oxide), reduction (single- or double-reduced), and whether or not coated with a plastic material.

All products that meet the written physical description are within the scope of this investigation unless specifically excluded. The following products are outside and/or specifically excluded from the scope of this investigation:

- Single reduced electrolytically chromium coated steel with a thickness 0.238 mm (85 pound base box) ($\pm 10\%$) or 0.251 mm (90 pound base box) ($\pm 10\%$) or 0.255 mm ($\pm 10\%$) with 770 mm (minimum width) (± 1.588 mm) by 900 mm (maximum length if sheared) sheet size or 30.6875 inches (minimum width) ($\pm 1/16$ inch) and 35.4 inches (maximum length if sheared) sheet size; with type MR or higher (per ASTM) A623 steel chemistry; batch annealed at T2 $\frac{1}{2}$ anneal temper, with a yield strength of 31 to 42 kpsi (214 to 290 Mpa); with a tensile strength of 43 to 58 kpsi (296 to 400 Mpa); with a chrome coating restricted to 32 to 150 mg/m²; with a chrome oxide coating restricted to 6 to 25 mg/m² with a modified 7B ground roll finish or blasted roll finish; with roughness average (Ra) 0.10 to 0.35 micrometers, measured with a stylus instrument with a stylus radius of 2 to 5 microns, a trace length of 5.6 mm, and a cut-off of 0.8 mm, and the measurement traces shall be made perpendicular to the rolling direction; with an oil level of 0.17 to 0.37 grams/base box as type BSO, or 2.5 to 5.5 mg/m² as type DOS, or 3.5 to 6.5 mg/m² as type ATBC; with electrical conductivity of static probe voltage drop of 0.46 volts drop maximum, and with electrical conductivity degradation to 0.70 volts drop maximum after stoving (heating to 400 degrees F for 100 minutes followed by a cool to room temperature).
- Single reduced electrolytically chromium- or tin-coated steel in the gauges of 0.0040 inch nominal, 0.0045 inch nominal, 0.0050 inch nominal, 0.0061 inch nominal (55 pound base box weight), 0.0066 inch nominal (60 pound base box weight), and 0.0072 inch nominal (65 pound base box weight), regardless of width, temper, finish, coating or other properties.
- Single reduced electrolytically chromium coated steel in the gauge of 0.024 inch, with widths of 27.0 inches or 31.5 inches, and with T-1 temper properties.
- Single reduced electrolytically chromium coated steel, with a chemical composition of 0.005% max carbon, 0.030% max silicon, 0.25% max manganese, 0.025% max phosphorous, 0.025% max sulfur 0.070% max aluminum, and the balance iron, with a metallic chromium layer of 70- 130 mg/m², with a chromium oxide layer of 5-30 mg/m², with a tensile strength of 260-440 N/mm², with an elongation of 28-48%, with a hardness (HR-30T) of 40-58, with a surface roughness of 0.5-1.5 microns Ra, with magnetic properties of Bm (kg) 10.0 minimum, Br (kg) 8.0 minimum, Hc (Oe) 2.5-

3.8, and MU 1400 minimum, as measured with a Riken Denshi DC magnetic characteristic measuring machine, Model BHU-60.

- Bright finish tin-coated sheet with a thickness equal to or exceeding 0.0299 inch, coated to thickness of $\frac{3}{4}$ pound (0.000045 inch) and 1 pound (0.00006 inch).
- Electrolytically chromium coated steel having ultra flat shape defined as oil can maximum depth of $\frac{5}{64}$ inch (2.0 mm) and edge wave maximum of $\frac{5}{64}$ inch (2.0 mm) and no wave to penetrate more than 2.0 inches (51.0 mm) from the strip edge and coilset or curling requirements of average maximum of $\frac{5}{64}$ inch (2.0 mm) (based on six readings, three across each cut edge of a 24 inches (61 cm) long sample with no single reading exceeding $\frac{4}{32}$ inch (3.2 mm) and no more than two readings at $\frac{4}{32}$ inch (3.2 mm)) and (for 85 pound base box item only: crossbuckle maximums of 0.001 inch (0.0025 mm) average having no reading above 0.005 inch (0.127 mm)), with a camber maximum of $\frac{1}{4}$ inch (6.3 mm) per 20 feet (6.1 meters), capable of being bent 120 degrees on a 0.002 inch radius without cracking, with a chromium coating weight of metallic chromium at 100 mg/m² and chromium oxide of 10 mg/m², with a chemistry of 0.13% maximum carbon, 0.60% maximum manganese, 0.15% maximum silicon, 0.20% maximum copper, 0.04% maximum phosphorous, 0.05% maximum sulfur, and 0.20% maximum aluminum, with a surface finish of Stone Finish 7C, with a DOS-A oil at an aim level of 2 mg/square meter, with not more than 15 inclusions/foreign matter in 15 feet (4.6 meters) (with inclusions not to exceed $\frac{1}{32}$ inch (0.8 mm) in width and $\frac{3}{64}$ inch (1.2 mm) in length), with thickness/temper combinations of either 60 pound base box (0.0066 inch) double reduced CADR8 temper in widths of 25.00 inches, 27.00 inches, 27.50 inches, 28.00 inches, 28.25 inches, 28.50 inches, 29.50 inches, 29.75 inches, 30.25 inches, 31.00 inches, 32.75 inches, 33.75 inches, 35.75 inches, 36.25 inches, 39.00 inches, or 43.00 inches, or 85 pound base box (0.0094 inch) single reduced CAT4 temper in widths of 25.00 inches, 27.00 inches, 28.00 inches, 30.00 inches, 33.00 inches, 33.75 inches, 35.75 inches, 36.25 inches, or 43.00 inches, with width tolerance of $\frac{1}{8}$ inch, with a thickness tolerance of 0.0005 inch, with a maximum coil weight of 20,000 pounds (9071.0 kg), with a minimum coil weight of 18,000 pounds (8164.8 kg), with a coil inside diameter of 16 inches (40.64 cm) with a steel core, with a coil maximum outside diameter of 59.5 inches (151.13 cm), with a maximum of one weld (identified with a paper flag) per coil, with a surface free of scratches, holes, and rust.
- Electrolytically tin coated steel having differential coating with 1.00 pound/base box equivalent on the heavy side, with varied coating equivalents in the lighter side (detailed below), with a continuous cast steel chemistry of type MR, with a surface finish of type 7B or 7C, with a surface passivation of 0.7 mg/square foot of chromium applied as a cathodic dichromate treatment, with coil form having restricted oil film weights of 0.3-0.4 grams/base box of type DOS-A oil, coil inside diameter ranging from 15.5 to 17 inches, coil outside diameter of a maximum 64 inches, with a maximum coil weight of 25,000 pounds, and with temper/coating/dimension combinations of: (1) CAT4 temper, 1.00/.050 pound/base box coating, 70 pound/base box (0.0077 inch) thickness, and 33.1875 inch ordered width; or (2) CAT5 temper, 1.00/0.50 pound/base box coating, 75 pound/base box (0.0082 inch) thickness, and 34.9375 inch or 34.1875 inch ordered width; or (3) CAT5 temper, 1.00/0.50 pound/base box coating, 107 pound/base box (0.0118 inch) thickness, and 30.5625 inch or 35.5625 inch ordered width; or (4) CADR8 temper, 1.00/0.50 pound/base box coating, 85 pound/base box (0.0093 inch) thickness, and 35.5625

inch ordered width; or (5) CADR8 temper, 1.00/0.25 pound/base box coating, 60 pound/base box (0.0066 inch) thickness, and 35.9375 inch ordered width; or (6) CADR8 temper, 1.00/0.25 pound/base box coating, 70 pound/base box (0.0077 inch) thickness, and 32.9375 inch, 33.125 inch, or 35.1875 inch ordered width.

- Electrolytically tin coated steel having differential coating with 1.00 pound/base box equivalent on the heavy side, with varied coating equivalents on the lighter side (detailed below), with a continuous cast steel chemistry of type MR, with a surface finish of type 7B or 7C, with a surface passivation of 0.5 mg/square foot of chromium applied as a cathodic dichromate treatment, with ultra flat scroll cut sheet form, with CAT5 temper with 1.00/0.10 pound/base box coating, with a lithograph logo printed in a uniform pattern on the 0.10 pound coating side with a clear protective coat, with both sides waxed to a level of 15-20 mg/216 sq. inch, with ordered dimension combinations of (1) 75 pound/base box (0.0082 inch) thickness and 34.9375 inch x 31.748 inch scroll cut dimensions; or (2) 75 pound/base box (0.0082 inch) thickness and 34.1875 inch x 29.076 inch scroll cut dimensions; or (3) 107 pound/base box (0.0118 inch) thickness and 30.5625 inch x 34.125 inch scroll cut dimension.
- Tin-free steel coated with a metallic chromium layer between 100-200 mg/m² and a chromium oxide layer between 5-30 mg/m²; chemical composition of 0.05% maximum carbon, 0.03% maximum silicon, 0.60% maximum manganese, 0.02% maximum phosphorous, and 0.02% maximum sulfur; magnetic flux density (Br) of 10 kg minimum and a coercive force (Hc) of 3.8 Oe minimum.
- Tin-free steel laminated on one or both sides of the surface with a polyester film, consisting of two layers (an amorphous layer and an outer crystal layer), that contains no more than the indicated amounts of the following environmental hormones: 1 mg/kg BADGE (BisPhenol – A Di-glycidyl Ether), 1 mg/kg BFDGE (BisPhenol – F Di-glycidyl Ether), and 3 mg/kg BPA (BisPhenol – A).

The merchandise subject to this investigation is currently classified in the Harmonized Tariff Schedule of the United States (HTSUS), under HTSUS subheadings 7210.11.0000, 7210.12.0000, 7210.50.0020, 7210.50.0090, 7212.10.0000, and 7212.50.0000 if of non-alloy steel and under HTSUS subheadings 7225.99.0090, and 7226.99.0180 if of alloy steel. Although the subheadings are provided for convenience and customs purposes, the written description of the scope of the investigation is dispositive.

Appendix II

List of Topics Discussed in the Issues and Decision Memorandum

- I. Summary
- II. Background
- III. Period of Investigation
- IV. Scope of the Investigation
- V. Changes Since the *Preliminary Determination*
- VI. Final Negative Determination of Critical Circumstances
- VII. Discussion of the Issues
 - Comment 1: Home Market Viability
 - Comment 2: Date of Sale
 - Comment 3: Physical Characteristics
 - Comment 4: U.S. Sales in 2023
 - Comment 5: Verification Schedule
 - Comment 6: Differential Pricing
- VIII. Recommendation

[FR Doc. 2024-00319 Filed: 1/9/2024 8:45 am; Publication Date: 1/10/2024]